

VARIO TightTec X and I

Pre-formed Sheeting for Corners

Parameter	Typical performance values		
Application/Intended use	Pre-formed profiles specially designed for simple and quick airtight sealing of junctions at internal and external edges and corners. e.g. on external walls, windows, doors and inner corners.		
Material/Specification			
Material	Non-ageing PE sheeting.		
Sheet thickness	Approx. 0.15 mm		
Contents/ Packaging	Product	Dimensions mm	Packaging Pieces
	TightTec X	200 x 400	60
	TightTec X	120 x 400	60
	TightTec I	200 x 400	60
Technical performance			
Diffusion-equivalent air layer thickness (s _d value)	50 m		
Site information			
	The profiles can be easily folded and fitted into the corner with the help of the dotted line markings. Airtight seams with ISOVER VARIO KM and VARIO KM Duplex UV climate membranes can be achieved by taping over with VARIO MultiTape .		

The information given in this Technical Data Sheet is correct to the best of our knowledge and experience at the time of publication. If not expressly agreed otherwise, this information does not represent a warranty in the legal sense of the word. As the state of our knowledge and experience is constantly changing, the information in this data sheet is subject to revision. We therefore kindly ask you to always use the latest issue of this Technical Data Sheet.

The product applications described in this data sheet cannot take the special circumstances of individual cases into account. Therefore carry out sufficient tests to ensure our products are suitable for the intended application. Please contact our ISOVER Technical Team if you have any questions.

All sales are based on our General Terms and Conditions.