

## VARIO – Moisture management for new and renovated constructions, perfect down to the finest detail

### Perfectly matched – VARIO System Components

Climate membrane	Properties	Uses
VARIO KM Duplex UV	non-woven, reinforced, water vapour regulating climate membrane. variable $s_d$ value 0.3 m to 5.0 m. highly tear resistant and easy to lay, thanks to guideline markings	For sealing the insulation layer in all building elements (floors, walls and roofs). Excellent moisture protection for new buildings and renovation work, of solid and lightweight construction
VARIO KM	moisture-regulating climate membrane. variable $s_d$ value, 0.2 m to 5.0 m	
Adhesive and sealing products	Properties	Adhesive and sealing products
VARIO KB1	single-sided adhesive tape with high bonding strength	Extra-wide for airtight bonding of seam overlaps in VARIO KM / VARIO KM Duplex UV climate membranes
VARIO DB	self-adhesive, rollable compressed tapes	For producing airtight joints in lightweight and solid construction combined with a clamping strip
VARIO DS	durable elastic, self-adhesive sealant in a cartridge or sausage bag	For producing perfect wind and airtight joints in VARIO KM / VARIO KM Duplex UV climate membrane
VARIO ProTape	durable elastic, self-adhesive sealant on a roll. 50% quicker to apply than with a cartridge	
VARIO MultiTape	Flexible and ductile adhesive tape with high bonding strength	For durable airtight joints in VARIO KM / VARIO KM Duplex UV climate membrane around roof windows, pipes, roof penetrations and at membrane overlaps
VARIO MultiTape SL	Flexible adhesive tape with split release strip	
VARIO SilverFast	Waterproof adhesive tape with strong bond for increased stability	For a range of bonding jobs inside and outside. Main uses include: bonding suspended ceilings, underlay, sarking and facade membranes
VARIO TightTec	Advanced design and with pre-marked membrane panels 200 x 400 mm 120 x 400 mm	For airtight seals of all types of corners, such as outer walls, outer walls, window, door, and inner corners
Mangete Passelec	Strongly adhesive, tear-resistant sleeve, 60 x 60 cm	For airtight penetration joints for all types of installation, conduits through VARIO KM / VARIO KM Duplex UV
VARIO Stos	Flexible pre-forms with strongly adhesive tape, 195 x 195 mm and 285 x 285 mm	
VARIO FS1	Elastic mineral wool, four-layer, faced with black PE film, 16 cm wide	For producing airtight joints and junctions in pitched roofs, and timber constructions, e.g. sealing tile flap to wall plate
VARIO FS2	Elastic mineral wool, four layer, faced with transparent PE film, 6 cm wide	For sealing windows in lightweight and solid constructions