

VARIO MultiTape SL Adhesive Tape

Parameter	Typical performance values		
Application/Intended use			
	<p>Single-sided flexible adhesive tape for producing airtight seals between ISOVER VARIO KM and VARIO KM Duplex UV climate membranes and roof windows, pipes and other building components. The split release strip makes it especially easy to install the tape in corners and difficult-to-access areas.</p> <p>Also ideally suited for a wide range of bonding jobs, both indoors and outdoors.</p>		
Suitable substrates	<p>PE and PA sheets, aluminium foils, Kraft papers, metals, plastics, hard wood materials (OSB boards, chipboards, etc.).</p> <p>The substrate must be dry and free of dust and grease.</p>		
Material/Specification			
Material	Double-layer structure comprising special mesh reinforced PE sheeting, with a solvent-free, modified acrylate adhesive.		
Contents/ Packaging	Width	Length	Rolls / Pack
	mm	m	Pieces
	60	25	10
Technical performance			
Temperature range	- 30°C to + 100°C		
Environmental information			
	Free of solvents, isocyanates, PVC, heavy metals and halogens.		
Site information			
Application temperature	From - 10°C upwards.		

The information given in this Technical Data Sheet is correct to the best of our knowledge and experience at the time of publication. If not expressly agreed otherwise, this information does not represent a warranty in the legal sense of the word. As the state of our knowledge and experience is constantly changing, the information in this data sheet is subject to revision. We therefore kindly ask you to always use the latest issue of this Technical Data Sheet.

The product applications described in this data sheet cannot take the special circumstances of individual cases into account. Therefore carry out sufficient tests to ensure our products are suitable for the intended application. Please contact our ISOVER Technical Team if you have any questions.

All sales are based on our General Terms and Conditions.