

VARIO ProTape Sealing Tape

Parameter	Typical performance values		
Application/Intended use			
	For producing airtight junctions between ISOVER VARIO KM and VARIO KM Duplex UV climate membranes and floors, ceilings and walls. Also ideal for use with PE vapour control membranes.		
Suitable substrates	PE and PA sheeting, aluminium foils, Kraft papers, metals, hard wood materials (OSB boards, chipboards, etc.). The substrate may be slightly damp (low residual moisture from the plaster), but must be free of dust and grease.		
Material/Specification			
Material	Special hotmelt PE sheeting with expanded acrylate dispersion adhesive.		
Contents/ Packaging	Width mm	Length m	Rolls / Pack Pieces
	25	10	5
Technical performance			
Resistance to wood preservatives	Resistant to water- or oil-based wood preservatives when in the fully reacted state.		
Resistance to ageing	Durable resistance indoors if correctly applied.		
Shelf life	Can be stored for 24 months at temperatures of < 30 °C in the original, unopened packaging.		
Temperature range	- 40°C to + 100°C		
Environmental information			
	Free of solvents, isocyanates, PVC, heavy metals and halogens.		
Site information			
Installation	VARIO ProTape can be applied with or without pressure lath.		
Application temperature	- 10°C to + 35 °C		

The information given in this Technical Data Sheet is correct to the best of our knowledge and experience at the time of publication. If not expressly agreed otherwise, this information does not represent a warranty in the legal sense of the word. As the state of our knowledge and experience is constantly changing, the information in this data sheet is subject to revision. We therefore kindly ask you to always use the latest issue of this Technical Data Sheet.

The product applications described in this data sheet cannot take the special circumstances of individual cases into account. Therefore carry out sufficient tests to ensure our products are suitable for the intended application. Please contact our ISOVER Technical Team if you have any questions.

All sales are based on our General Terms and Conditions.