

VARIO SilverFast Adhesive Tape

Parameter	Typical performance values		
Application/Intended use			
	<p>Single-sided adhesive tape used outdoors for producing durable airtight and water-repellent bonds between the overlapping seams of underlay, sarking and facade membranes, as well as sealing junctions between the membranes and roof windows, pipes and other building components.</p> <p>Also ideally suited for bonding overlapping seams in VARIO climate membranes, both indoors and outdoors.</p>		
Suitable substrates	<p>PE and PA sheets, aluminium foils, PP and paper, Kraft papers, metals, plastics, wood and hard wood-based materials (OSB boards, chipboards, etc.). Underlay membranes are suitable if installed according to roofing trade technical guidelines.</p> <p>The substrate must be sound, dry and free of dust and grease.</p>		
Material/Specification			
Material	Special mesh-reinforced PE sheeting with solvent-free, modified acrylate adhesive.		
Contents/ Packaging	Width mm	Length m	Rolls / Pack Pieces
	60	25	10
Technical performance			
UV resistance	At least 12 months with direct exposure to solar radiation.		
Temperature range	- 30°C to + 100°C		
Environmental information			
	Free of solvents, isocyanates, PVC, heavy metals and halogens.		
Site information			
Application temperature	From - 10°C upwards		

The information given in this Technical Data Sheet is correct to the best of our knowledge and experience at the time of publication. If not expressly agreed otherwise, this information does not represent a warranty in the legal sense of the word. As the state of our knowledge and experience is constantly changing, the information in this data sheet is subject to revision. We therefore kindly ask you to always use the latest issue of this Technical Data Sheet.

The product applications described in this data sheet cannot take the special circumstances of individual cases into account. Therefore carry out sufficient tests to ensure our products are suitable for the intended application. Please contact our ISOVER Technical Team if you have any questions.
All sales are based on our General Terms and Conditions.